



Kimball Electronics Group

1600 Royal Street

GO-149

Jasper, IN 47549 812-634-9497

Functional Acknowledgment

EDI Transaction 997

Specifications

X12 Standard 004010

Inbound to Kimball

997

Functional Acknowledgment

Functional Group=FA

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	ISA	Interchange Control Header	M	1			Used
	GS	Functional Group Header	M	1			Used

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1		N1/010	Must use
020	AK1	Functional Group Response Header	M	1		N1/020	Must use
LOOP ID - AK2					999999	N1/030L	
030	AK2	Transaction Set Response Header	O	1		N1/030	Used
060	AK5	Transaction Set Response Trailer	M	1			Must use
070	AK9	Functional Group Response Trailer	M	1			Must use
080	SE	Transaction Set Trailer	M	1			Must use

Not Defined:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
	GE	Functional Group Trailer	M	1			Used
	IEA	Interchange Control Trailer	M	1			Used

ISA

Interchange Control Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 16

User Option (Usage): Used

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ISA01	I01	Authorization Information Qualifier Description: Code to identify the type of information in the Authorization Information	M	ID	2/2	Must use
		Code Name 00 No Authorization Information Present (No Meaningful Information in I02)				
ISA02	I02	Authorization Information Description: Information used for additional identification or authorization of the interchange sender or the data in the interchange; the type of information is set by the Authorization Information Qualifier (I01)	M	AN	10/10	Must use
ISA03	I03	Security Information Qualifier Description: Code to identify the type of information in the Security Information	M	ID	2/2	Must use
		Code Name 00 No Security Information Present (No Meaningful Information in I04)				
ISA04	I04	Security Information Description: This is used for identifying the security information about the interchange sender or the data in the interchange; the type of information is set by the Security Information Qualifier (I03)	M	AN	10/10	Must use
ISA05	I05	Interchange ID Qualifier Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.	M	ID	2/2	Must use
ISA06	I06	Interchange Sender ID Description: Identification code published by the sender for other parties to use as the receiver ID to route data to them; the sender always codes this value in the sender ID element	M	AN	15/15	Must use
ISA07	I05	Interchange ID Qualifier Description: Qualifier to designate the system/method of code structure used to designate the sender or receiver ID element being qualified All valid standard codes are used.	M	ID	2/2	Must use
ISA08	I07	Interchange Receiver ID Description: Identification code published by the receiver of the data; When sending, it is used by the sender as their sending ID, thus other parties sending to them will use this as a receiving ID to route data to them	M	AN	15/15	Must use
ISA09	I08	Interchange Date Description: Date of the interchange	M	DT	6/6	Must use
ISA10	I09	Interchange Time Description: Time of the interchange	M	TM	4/4	Must use
ISA11	I10	Interchange Control Standards Identifier Description: Code to identify the agency responsible for the control standard used by the message that is enclosed by the interchange header and trailer	M	ID	1/1	Must use

997 Version 004010

All valid standard codes are used.

ISA12	I11	Interchange Control Version Number Description: This version number covers the interchange control segments	M	ID	5/5	Must use
		Code Name 00401 Draft Standards for Trial Use Approved for Publication by ASC X12 Procedures Review Board through October 1997				
Ref	Id	Element Name	Req	Type	Min/Max	Usage
ISA13	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	N0	9/9	Must use
ISA14	I13	Acknowledgment Requested Description: Code sent by the sender to request an interchange acknowledgment (TA1)	M	ID	1/1	Must use
		Code Name 0 No Acknowledgment Requested				
Ref	Id	Element Name	Req	Type	Min/Max	Usage
ISA15	I14	Usage Indicator Description: Code to indicate whether data enclosed by this interchange envelope is test, production or information	M	ID	1/1	Must use
		Code Name P Production Data T Test Data				
Ref	Id	Element Name	Req	Type	Min/Max	Usage
ISA16	I15	Component Element Separator Description: Type is not applicable; the component element separator is a delimiter and not a data element; this field provides the delimiter used to separate component data elements within a composite data structure; this value must be different than the data element separator and the segment terminator	M	AN	1/1	Must use

GS

Functional Group Header

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 8

User Option (Usage): Used

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GS01	479	Functional Identifier Code Description: Code identifying a group of application related transaction sets	M	ID	2/2	Must use
		Code Name FA Functional Acknowledgment (997)				
GS02	142	Application Sender's Code Description: Code identifying party sending transmission; codes agreed to by trading partners	M	AN	2/15	Must use
GS03	124	Application Receiver's Code Description: Code identifying party receiving transmission. Codes agreed to by trading partners	M	AN	2/15	Must use
GS04	373	Date Description: Date expressed as CCYYMMDD	M	DT	8/8	Must use
GS05	337	Time Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)	M	TM	4/8	Must use
GS06	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use
GS07	455	Responsible Agency Code Description: Code used in conjunction with Data Element 480 to identify the issuer of the standard	M	ID	1/2	Must use
		Code Name X Accredited Standards Committee X12				
GS08	480	Version / Release / Industry Identifier Code Description: Code indicating the version, release, subrelease, and industry identifier of the EDI standard being used, including the GS and GE segments; if code in DE455 in GS segment is X, then in DE 480 positions 1-3 are the version number; positions 4-6 are the release and subrelease, level of the version; and positions 7-12 are the industry or trade association identifiers (optionally assigned by user); if code in DE455 in GS segment is T, then other formats are allowed	M	AN	1/12	Must use
		Code Name 004010 Draft Standards Approved for Publication by ASC X12 Procedures Review Board through October 1997				

Semantics:

- GS04 is the group date.
- GS05 is the group time.
- The data interchange control number GS06 in this header must be identical to the same data element in the associated functional group trailer, GE02.

997 Version 004010

Comments:

1. A functional group of related transaction sets, within the scope of X12 standards, consists of a collection of similar transaction sets enclosed by a functional group header and a functional group trailer.

ST

Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set	M	ID	3/3	Must use
		Code Name 997 Functional Acknowledgment				
ST02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

AK1

Functional Group Response Header

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AK101	479	Functional Identifier Code Description: Code identifying a group of application related transaction sets All valid standard codes are used.	M	ID	2/2	Must use
AK102	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	NO	1/9	Must use

Semantics:

- AK101 is the functional ID found in the GS segment (GS01) in the functional group being acknowledged.
- AK102 is the functional group control number found in the GS segment in the functional group being acknowledged.

Loop AK2

Pos: 030	Repeat: 999999
Optional	
Loop: AK2	Elements: N/A

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
030	AK2	Transaction Set Response Header	O	1		Used
060	AK5	Transaction Set Response Trailer	M	1		Must use

AK2

Transaction Set Response Header

Pos: 030	Max: 1
Heading - Optional	
Loop: AK2	Elements: 2

User Option (Usage): Used

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AK201	143	Transaction Set Identifier Code Description: Code uniquely identifying a Transaction Set All valid standard codes are used.	M	ID	3/3	Must use
AK202	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Semantics:

1. AK201 is the transaction set ID found in the ST segment (ST01) in the transaction set being acknowledged.
2. AK202 is the transaction set control number found in the ST segment in the transaction set being acknowledged.

AK5

**Transaction Set Response
Trailer**

Pos: 060	Max: 1
Heading - Mandatory	
Loop: AK2	Elements: 1

User Option (Usage): Must use

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AK501	717	Transaction Set Acknowledgment Code Description: Code indicating accept or reject condition based on the syntax editing of the transaction set All valid standard codes are used.	M	ID	1/1	Must use

AK9

Functional Group Response Trailer

Pos: 070	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
AK901	715	Functional Group Acknowledge Code Description: Code indicating accept or reject condition based on the syntax editing of the functional group	M	ID	1/1	Must use
		Code Name A Accepted				
AK902	97	Number of Transaction Sets Included Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M	N0	1/6	Must use
AK903	123	Number of Received Transaction Sets Description: Number of Transaction Sets received	M	N0	1/6	Must use
AK904	2	Number of Accepted Transaction Sets Description: Number of accepted Transaction Sets in a Functional Group	M	N0	1/6	Must use

Comments:

1. If AK901 contains the value "A" or "E", then the transmitted functional group is accepted.

SE

Transaction Set Trailer

Pos: 080	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments Description: Total number of segments included in a transaction set including ST and SE segments	M	N0	1/10	Must use
SE02	329	Transaction Set Control Number Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set	M	AN	4/9	Must use

Comments:

- SE is the last segment of each transaction set.

GE

Functional Group Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Used

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
GE01	97	Number of Transaction Sets Included Description: Total number of transaction sets included in the functional group or interchange (transmission) group terminated by the trailer containing this data element	M	N0	1/6	Must use
GE02	28	Group Control Number Description: Assigned number originated and maintained by the sender	M	N0	1/9	Must use

Semantics:

1. The data interchange control number GE02 in this trailer must be identical to the same data element in the associated functional group header, GS06.

Comments:

1. The use of identical data interchange control numbers in the associated functional group header and trailer is designed to maximize functional group integrity. The control number is the same as that used in the corresponding header.

IEA

Interchange Control Trailer

Pos:	Max: 1
Not Defined - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Used

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
IEA01	I16	Number of Included Functional Groups Description: A count of the number of functional groups included in an interchange	M	N0	1/5	Must use
IEA02	I12	Interchange Control Number Description: A control number assigned by the interchange sender	M	N0	9/9	Must use

Inbound 997 Sample Data

ISA*00* *00* *01*ABC123 *12*8126344400HARB *050413*1121*U*00200*000002025*0*P*>~
GS*FA*ABC123*KIKEG01*20050413*1121*1950*X*004010~
ST*997*0001~
AK1*PO*125~
AK2*850*0001~
AK5*A~
AK2*850*0002~
AK5*A~
AK2*850*0003~
AK5*A~
AK2*850*0004~
AK5*A~
AK9*A*4*4*4~
SE*12*0001~
GE*1*1950~
IEA*1*000002025~